

WG-640 Lite Cut 3

PRODUCT TECHNICAL SHEET



The newest cut-resistant glove from WG-640 Lite Cut 3 combines our signature flexibility, dexterity and grip, while offering excellent cut resistance (ISO 13997 grade C). Developed using our proprietary high performance blend of reinforced nylon and mineral fibre, WG-640 Lite Cut 3 is the ideal glove for all your applications requiring medium-level cut resistance in dry, humid and oily environments.

APPLICATIONS

- installation and handling of sharp parts or objects
- automotive
- metallurgy
- steel industry
- recycling
- industrial maintenance
- sorting
- assemblage
- assembly

INFORMATION

Coating

Nitrile single dip, Palm fit

Liner

Nylon and Technical Fiber, Grey / Black

Gauge

13

Packaging

12 paires / polybag

144 paires / box

DIMENSIONS Tolerance ± 5 %

SIZE	6 / XS	7 / S	8 / M	9 / L	10 / XL	11 / XXL
Hem Color	Red	Purple	Black	Grey	Yellow	Beige
Overall Length (mm)	220	232	244	257	260	272
Palm width (mm)	84	90	94	99	103	110
Length of middle finger (mm)	68	73	75	80	80	88
Thickness (µm)	1320	1310	1330	1320	1350	1360
Weight (g/paire)	47.79	57.58	60.99	67.14	71.34	78.59
Liner Weight (g/paire)	35.54	44	45.43	49.62	52.02	56.9
Coating Weight (g/paire)	12.3	13.6	15.6	17.5	19.3	22.1

PROTECTION

- Cut-resistance

NORMS



EN388:

2016



4342C

DOCUMENTS

You can also upload on our website :

- Product technical sheet
- EU certificate
- Declaration of Conformity
- Food contact information
- User instructions

CARTON INFORMATION

Carton Volume (m,m ³)	Length 0.530 x Width 0.315 x Height 0.280 : Volume 0.047 (m ³)					
Carton Net Weight (kg)	6	6.5	7.0	7.5	8.9	9.5
Carton Gross Weight (kg)	7	7.5	8.0	8.5	9.9	10.5